

AV248A14 / AV264A19

Air Hydraulic Riveter



AV248A14

Features

- Blind Rivet Capacity: up to 3/16"(4.8mm)
- Nosepieces: 2.4mm, 3.2mm, 4.0mm, 4.8mm
- Acceptable rivet material: Aluminum/Steel/Stainless
- Working Pressure: 60~100 PSI
- Jaw Option: 2 or 3 Jaws



AV264A19

Features

- Blind Rivet Capacity: up to 1/4"(6.4mm)
- Nosepieces: 2.4mm, 3.2mm, 4.0mm, 4.8mm, 6.4mm
- Acceptable rivet material: Aluminum/Steel/Stainless
- Working Pressure: 80~100 PSI
- Jaw Option: 2 or 3 Jaws

Tool Specifications

AV248A14 : 10 Pcs/18 Kg/19 Kg/1.85' • AV264A19 : 6 Pcs/16.0 Kg/17.0 Kg/2.03'

Model No.	Air Inlet	Hose Size I.D.	Avg/Air Con.	Traction Power	Stroke Length	Blind Rivet Setting Capacity-mm	Max Rivet Capacity	Net Weight
AV248A14	1/4"	1/4"	3.5CFM	2680 Lbs	14mm	3/32"-3/16"(2.4-4.8mm)	AL. & Steel: 4.8mm	1.5 kgs
			99 L/Min	1219 Kgs		Stainless:3.2mm	3.3 LBs	
AV264A19	1/4"	1/4"	4.2CFM	4166 Lbs	19mm	3/32"-1/4"(2.4-6.4mm)	AL. & Steel: 6.4mm	2.0 kgs
			119 L/Min	1894 Kgs		Stainless:4.8mm	4.3 LBs	

APACH INDUSTRIAL CO., LTD.

176 Industrial 9th Rd., Tali Dist., Taichung City, Taiwan 41208
 Tel +886 4 2271 2835 Fax +886 4 2271 4840
 www.apach-tools.com info@apach.com.tw

