

AW200D / AW200E / AW200F

1" Lightweight Air Impact Wrench



Features

- Mechanism: Twin Hammer / pinless / pinclutch optional
- Highest durable Japanese steel anvil (standard & 6" optional)
- Top exhaust or bottom exhaust
- Forward & Reverse : 3 positions for each side
- Heavy duty casting of housing
- Inside or outside trigger available
- Left / Right handle available
- Available for kit set :
(sockets: 21, 22, 24, 27, 30, 36, 38, 41mm x 90L)



Boat



Truck



Industry
Assembling
Line



Agriculture
Machine



Structure

Tool Specifications

	Square Drive	Bolt Capacity	Avg/Air Con.	Air Inlet	Air Pressures	Hose Size I.D.	Working Torque	Max Torque 10 Sec.	Free Speed	Vibration	Sound Pressure Level	Overall Length	Net Weight	
													2" Anvil	6" Anvil
AW200D Twin Hammer	1"	1-3/8" M33	6.94 CFM 196 L/Min	1/2"	6.2 Bar 90 psi	1/2"	2200 FT-LB 2983 N.m.	2700 FT-LB 3661 N.m.	5500 RPM	9.49 m/s ²	100.1 Dba	490 mm 19-3/8"	6.65 kg 14.66 LB	7.72 kg 17.02LB
AW200E Pinless							2200 FT-LB 2983 N.m.	2600 FT-LB 3525 N.m.					7.64kg 16.84 LB	8.58 kg 18.92 LB
AW200F PinClutch							2000 FT-LB 2712 N.m.	2500 FT-LB 3390 N.m.					7.5 kg 16.53 LB	8.35 kg 18.41 LB