

LPB & LPS Series

Pneumatic Foot Bottomers



▲ Features

- Suggested for High Volume Production Outputs –50 to 100 Carton Bottoms Per Hour
- Equipped with A Safety Foot Pedal

▲ Mechanical Foot Bottomers Are Also Available:

Bottomers	Side Bottomers	Staple Type
LMB-19SW	LPS-19SW	SW7437 strip
LMB-22A	LPS-22A	A strip
LPB-22C	LPS-22C	C strip
LPB-229040	LPS-229040	9040 strip

▲ Fasteners

Bottomers	Side Bottomers	Staple Type	Crown	Length
LPB-19SW	LPS-19SW	SW7437 strip	34.5 mm 1 3/8"	15 & 18 mm 5/8 & 3/4"
LPB-22A	LPS-22A	A strip	34.7 mm 1 3/8"	15, 18 & 22 mm 5/8, 3/4 & 7/8"
LPB-22C	LPS-22C	C strip	32 mm 1 1/4"	15, 18 & 22 mm 5/8, 3/4 & 7/8"
LPB-229040	LPS-229040	9040 strip	34.5 mm 1 3/8"	15, 18 & 22 mm 5/8, 3/4 & 7/8"

▲ Tool Specifications

Weight	Dimensions (L x W x H)	Operating Pressure	Lead Capacity
22.7 kg	830 x 600 x 1245 mm	5.5 - 6 kg / cm ²	200
50 lbs	32.6 x 23.6 x 49"	80 - 85 psi	200

APACH INDUSTRIAL CO., LTD.

176 Industrial 9th Rd., Tali Dist., Taichung City, Taiwan 41280
 Tel +886 4 2491 5576 Fax +886 4 2491 5580
www.apach.com.tw

